

Nooteboom

4-axle semi-lowbed trailer extendable 15.6 m

+ ramps

GENERAL

ID number	O000080
Brand	Nooteboom
Type	4-axle semi-lowbed trailer extendable 15.6 m + ramps
Chassis number	XMROSD00090000080
1st Registration Date	01-01-2009
Country of registration	UK
Dimensions	1330x252x360 cm

POWERTRAIN

ABS 

CHASSIS

Empty weight	12380 Kg.
Gross weight	48400 kg design weight
Kingpin height	130 cm

TYRES

Tyre size axle 1	205/65R17.5
Tyre size axle 2	205/65R17.5
Tyre size axle 3	205/65R17.5
Tyre size axle 4	205/65R17.5



ADDITIONAL INFO

4-axle extendable semi-lowbed trailer
OSD-50-04V, Load bed extends 640 cm, 2
Steering axles (3, 4), Lift axle (1st), ABS,
Air suspension, Dual tyres, Tyre size
205/65R17.5, Hydraulic loading ramps //
DIMENSIONS // Load bed length min. 920
cm, max. 1560 cm, Load bed height 78
cm, Load bed width 252 cm, Max. load bed
width 302 cm, Coupling centre to rearmost
part: min. 1170 cm, max. 1840 cm,
Gooseneck length 390 cm, Kingpin height
130 cm, Axle spacing 1-2: 272 cm, Axle
spacing 2-3-4: 136 cm // WEIGHTS // Max.
gross trailer weight: 64200 kg at 12 mph,
54780 kg at 20-25 mph, 51160 kg at 30
mph, 49700 kg at 35 mph, 49120 kg at 40
mph, Max. kingpin load 23400 kg - 12720
kg, Max. weight per axle: 10200 - 7600 kg
(weights under UK special types provision;
max. gross design weight 48400 kg), Total
shipment dimensions 1330x252x360 cm
incl. ramps

AXLES

Number of axles	4
Brand axles	Bpweco
Drum brake	✓
Suspension axle 1	Air suspension
Suspension axle 2	Air suspension
Suspension axle 3	Air suspension
Suspension axle 4	Air suspension
Lift axle Axle 1	✓
Steering axle, Axle 3	✓
Steering axle, Axle 4	✓

SUPERSTRUCTURE

Make superstructure	Nooteboom
Platform	✓

EXCEPTIONAL TRANSPORT

Extendable	✓
Max. length	1560 cm
Extendable width	✓
Max width	302 cm
Ramp length	285 cm
Load bed length	920
Goose neck length	390 cm
Axle plateau length	Min. 920 cm, max. 1560 cm
Hydraulic ramps	✓